



Off the road tyres.  
Off the chart endurance.



**STURDY, LONG-LASTING OTR TYRES FOR:**  
Earthmovers, Graders, Loaders, Dozers, Compactors, Container Handlers/Stackers, Underground Mining & Other Applications

ESPAÑOL | ABOUT US | QUOTE REQUEST

**ZIGGURAT E3/L3**

Download PDF



| [back to E3/L3 information](#) |

SIZE	PATTERN	QTY PER 40'HC	STD RIM	INFLATED DIMENSION (mm)		MAX LOAD (kg)		INFLATION PRESSURE (kpa)		
				SECTION WIDTH	OVERALL DIAM	SINGLE	DOUBLE	SINGLE	DOUBLE	
14.00-24	TL	E3/L3	120	10	375	1370	4580	6030	630	--
							5040	6640	740	
							6420	7150	840	
1600-24	TL	E3/L3	100	11.25/2.0	430	1490	5450	--	400	--
							6000		475	
15.5-25	TL	E3/L3	120	12.00/1.3	395	1275	2580	5300	250	390
							2980	6340	320	530
16.00-25	TL	E3/L3	90	11.25/2.0	430	1490	6050	10600	475	650
							6700	11500	575	750
							7300	12500	650	875
							7750	13600	725	975
17.5-25	TL	E3/L3	90	14.00/1.5	445	1350	3120	5980	225	350
							3600	7020	320	490
							4050	7620	390	530
20.5-25	TL	E3/L3	64	17.00/2.0	520	1490	4500	6700	200	250
							5450	8250	280	350
							6000	9500	350	460
							6700	10300	400	525
							7500	11500	475	625
23.5-25	TL	E3/L3	50	19.50/2.5	595	1615	6150	9500	250	320
							7300	10900	280	390
							8000	12500	350	475
							8750	13600	400	550
26.5-25	TL	E3/L3	36	22.00/3.0	675	1750	7300	11500	200	275
							8250	13200	250	350
							9250	14000	300	400
							10000	15500	350	475
							11200	17000	425	550
29.5-25	TL	E3/L3	26	25.00/3.5	750	1875	8000	12900	175	250
							10000	15000	250	325
							11500	17500	325	425
29.5-29	TL	E3/L3	24	25.00/3.5	750	1975	10600	16000	250	325
							12600	19000	325	425
							14000	21200	400	525
							15000	23600	475	625
18.00-25	TL	E3/L3	60	13.00/2.5	495	1615	8000	13600	500	650
							8750	15000	475	750
							9250	16000	625	850
							9750	17000	700	950
33.25-35	TL	E3/L3		27.00/3.5	845	2240	25700		450	



Copyright 2006 XTIRE, Inc. · All rights reserved.