



Off the road tyres.
Off the chart endurance.



STURDY, LONG-LASTING OTR TYRES FOR:
Earthmovers, Graders, Loaders, Dozers, Compactors, Container Handlers/Stackers, Underground Mining & Other Applications

ESPAÑOL | ABOUT US | QUOTE REQUEST

ZIGGURAT L301, L302, L303

Download PDF



| [back to L301-3 information](#) |



L-301

Pneumatic shaped solid tyre

SIZE	PATTERN	RIM	CLICK	Overall Diameter (mm)	Section Width (mm)	Maximum Tire Load Rating(kg)						(kg) 16km/h Other Vehicles
						10km/h		16km/h		25km/h		
						DRIVE	STEER	DRIVE	STEER	DRIVE	STEER	
15*41/2-8	L-301	3.25		380	106	905	725	875	655	805	605	625
15*41/2-8	L-301	3.00	CLICK	380	106	905	725	875	655	805	605	625
5.00-8	L-301	3.00	CLICK	469	126	1210	970	1175	880	1095	820	840
16*6-8	L-301	4.33	CLICK	418	156	1500	1200	1445	1085	1345	1010	1035
18*7-8	L-301	4.33	CLICK	457	154	2350	1880	2265	1700	2110	1585	1620
21*8-9	L-301	6.00	CLICK	535	189	2810	2250	2715	2035	2530	1895	1940
23*9-10	L-301	6.50	CLICK	597	230	4005	3205	3845	2885	3605	2705	2765
27*10-12	L-301	8.00	CLICK	683	236	4465	3570	4315	3235	4020	3015	3080
6.00-9	L-301	4.00	CLICK	545	140	1920	1535	1855	1390	1730	1295	1325
6.50-10	L-301	5.00	CLICK	597	157	2640	2110	2545	1910	2370	1780	1820
200/50-10	L-301	6.50	CLICK	458	198	2370	1900	2290	1720	2135	1605	1630
7.00-9	L-301	5.00		578	170	2730	2015	2605	1925	2370	1750	1785
7.00-12	L-301	5.00	CLICK	683	168	3015	2410	2910	2185	2710	2035	2075
7.00-15	L-301	5.50	CLICK	759	178	3590	2870	3465	2600	3225	2420	2475
7.00-15	L-301	6.00		759	178	3590	2870	3465	2600	3225	2420	2475
7.50-15	L-301	5.50		774	215	3690	2950	3425	2570	3190	2395	2450
7.50-15	L-301	6.00		774	215	3690	2950	3425	2570	3190	2395	2450
7.50-15	L-301	6.50		774	215	3690	2950	3425	2570	3190	2395	2450
7.50-16	L-301	5.50		819	181	3910	3130	3780	2835	3520	2640	2700
7.50-16	L-301	6.00		819	181	3910	3130	3780	2835	3520	2640	2700
8.00-16	L-301	5.50		825	206	4175	3335	4035	3020	3760	2800	2885
8.25-15	L-301	6.50	CLICK	847	205	4940	3950	4765	3575	4440	3330	3405
8.25-12	L-301	6.50		735	206	3325	2660	3215	2410	2995	2245	2295
8.15-15	L-301	7.00	CLICK	706	207	4090	3270	3945	2960	3675	2755	2820
8.25-20	L-301	6.50		992	218	5425	4340	5420	3930	4880	3735	3475
7.50-20	L-301	6.50		935	218	5165	4130	4985	3740	4640	3480	3560
250-15	L-301	7.00	CLICK	735	226	4365	3490	4220	3160	3930	2955	3010
250-15	L-301	7.50	CLICK	735	226	4365	3490	4220	3160	3930	2955	3010
9.00-16	L-301	6.50		884	218	5135	4110	4965	3725	4625	3470	3550
300-15	L-301	8.00	CLICK	838	258	5990	4790	5780	4335	5380	4035	4130
28*12.5-15	L-301	9.75		706	300	5735	4590	5540	4165	5170	3890	3955
32*12.1-15	L-301	9.75	CLICK	823	301	7120	5700	6880	5170	6410	4820	4910
9.00-20	L-301	6.50		1028	228	6450	5160	6225	4675	5805	4255	4450

3.00-15	L-301	8.50		884	278	5135	4170	4985	5725	4625	3470	3350
28*12.5-15	L-301	9.75		706	300	5735	4590	5540	4165	5170	3890	3955
32*12.1-15	L-301	9.75	CLICK	823	301	7120	5700	6880	5170	6410	4820	4910
9.00-20	L-301	6.50		1038	238	6450	5160	6235	4675	5805	4355	4450
9.00-20	L-301	7.00		1038	238	6450	5160	6235	4675	5805	4355	4450
10.00-20	L-301	7.50		1073	252	7240	5795	6995	5245	6510	4885	4995
10.00-20	L-301	8.00		1073	252	7240	5795	6995	5245	6510	4885	4995
11.00-20	L-301	8.00		1058	277	7560	6050	7300	5490	6810	5120	5210
12.00-20	L-301	8.00		1146	290	8445	6755	8105	6080	7600	5700	5825
12.00-20	L-301	8.50		1146	290	8445	6755	8105	6080	7600	5700	5825



L-303 Pneumatic shaped solid tyre

SIZE	PATTERN	RIM	CLICK	Overall Diameter (mm)	Section Width (mm)	Maximum Tire Load Rating(kg)						(kg) 16km/h Other Vehicles
						10km/h		16km/h		25km/h		
						DRIVE	STEER	DRIVE	STEER	DRIVE	STEER	
4.00-8	L-303	3.00		423	115	1055	845	1020	765	950	715	730
4.00-8	L-303	3.75		423	115	1055	845	1020	765	950	715	730



L-302 Pneumatic shaped solid tyre

SIZE	PATTERN	RIM	CLICK	Overall Diameter (mm)	Section Width (mm)	Maximum Tire Load Rating(kg)						(kg) 16km/h Other Vehicles
						10km/h		16km/h		25km/h		
						DRIVE	STEER	DRIVE	STEER	DRIVE	STEER	
15*41/2-8	L-302	3.00	CLICK	380	106	905	725	875	655	805	605	625
5.00-8	L-302	3.00	CLICK	469	126	1210	970	1175	880	1095	820	840
18*7-8	L-302	4.33	CLICK	457	154	2350	1880	2265	1700	2110	1585	1620
23*9-10	L-302	6.50	CLICK	597	230	4005	3205	3845	2885	3605	2705	2765
6.00-9	L-302	4.00	CLICK	545	140	1920	1535	1855	1390	1730	1295	1325
6.50-10	L-302	5.00	CLICK	597	157	2640	2110	2545	1910	2370	1780	1820
7.00-12	L-302	5.00	CLICK	683	168	3015	2410	2910	2185	2710	2035	2075
8.25-15	L-302	6.50	CLICK	847	205	4940	3950	4765	3575	4440	3330	3405
8.15-15	L-302	7.00	CLICK	706	207	4090	3270	3945	2960	3675	2755	2820
250-15	L-302	7.00	CLICK	735	226	4365	3490	4220	3160	3930	2955	3010
300-15	L-302	8.00	CLICK	838	258	5990	4790	5780	4335	5380	4035	4130

